

AW-5809 Portable Bluetooth Receipt Printer



Specifications

| | |
|-------------------|---|
| Interfaces | USB / Bluetooth 4.0 |
| Print Comand | ESC/POS |
| Print Method | Thermal Line Printing |
| Print Speed | 70mm/sec |
| Resolution | 203DPI (8dot/mm) |
| No. of Total Dots | 384 dots/Line |
| Print Width | 48mm |
| Character Size | 1.5 x 3.0mm (W x H)/3.0 x 3.0mm (W x H) |
| Print Font | 12 x 24; 24x 24 |
| Compatible OS | Windows Systems ; Android & IOS Operate Systems |

Paper

| | |
|-----------------|----------------------------|
| Type | Roll Paper |
| Width | 57.5± 0.5mm |
| Roll Diameter | $\varphi \leq 40\text{mm}$ |
| Paper Thickness | 0.06-0.08mm |

Electrical

| | |
|---------------------|---|
| Battery | 7.4VDC/2000mA |
| Charging mode | DC 5V/2A |
| Standby Time | 4 days after fully charged |
| Continuous Printing | 120 pieces Thermal Roll for fully charged battery |

Physical

| | |
|---------------|--|
| Dimension | 112*83*54mm |
| Unit Weight | 440g (including accessories: lithium-ion batteries, cable, test paper) |
| Carton Size | 47x38x34cm |
| GW per carton | 18kg (40pcs/CTN) |

Environmental

| | |
|--------------|----------------------------|
| Temperature | Working: -10 to 50 Degrees |
| Humidity | Working: 10%-90% |
| Warantty | 12 months at least |
| Certificates | CE& FCC ROHS ISO9001:2008 |