

AW-5890K Thermal Receipt Printer



Specifications

Interfaces	USB / USB+Bluetooth (Optional)
Printing Command	ESC/POS
Printing Method	Thermal Line Printing, support NV LOGO print
Printing Speed	90mm/sec (max)
Printing Density	384 dots/line
Character set	GB18030 (Simplified Chinese)
Print Font	84dot/Line ; ANK Character Font A:12*24 dots,1.5(W)*3.0(H)mm Chinese simplified/traditional:24*24 dots,3.0(W)*3.0(H)mm Printer Character: GB one/two Chinese character 24*24 dots, Support Taiwan,Hong kong traditional
Character per line	Font A-32 lines/Font B-42 lines/Chinese-16 lines
Input buffer	32 Kbytes / 64 Kbytes
Printer Head Life	100KM
Printer Driver	Windows / Linux / MAC / OPOS

Paper

Paper Type	Thermal Roll Paper
Paper Width	57.5±0.5mm
Paper Roll Diameter	Φ 50mm
Paper Thickness	0.06-0.08mm
Paper Out Detection	Support
Paper Cut	By hand

Electrical

Adapter Voltage	DC 12V/3A
Cash Drawer Control	12V/1A

Package

Printer Dimension	175*130*110mm (L*W*H)
Unit Weight	0.8kgs (with accessories)
Pieces Per CTN	18 Pieces
Printer Color	Black or White
Carton Weight	15kgs

Working Environment

Temperature	Working: 0~45°C
Humidity	Humidity: 10%-80%

Accessories

USB Cable	1 Piece
Thermal Roll	1 Piece
Manual	1 Piece
Power Cable	1 Piece