

AW-8108

Handheld CCD Barcode Scanner



Technology

Scan type	Linear Image CCD
Interface	USB/RS232/PS2
Scan Speed	300times/second
Resolution	4mil
Depth of Scan Field	10-600mm
Support Symbologies	UPC-A, UPC-E, EAN-8, EAN-13, ISSN, ISBN, Code 128, GS1-128, ISBT 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Standard 2 of 5 (IATA), Codabar (NW-7), Plessey, MSI Plessey, RSS, China Post, etc..
Operation	Manual/ Auto Continue Scan
Decode Error Rate	Less than 1/5 million
Scan Angel	Skew $\pm 50^\circ$, Pitch $\pm 50^\circ$, Roll $\pm 30^\circ$
Print contrast	25%

Electronical

Voltage	5V
Working Current	80mA
Scanner Material	Eco-friendly, ABS+Rubber

Environmental

Operation Temperature	-20 °C - 45°C
Storage Temperature	-20 °C - 45°C
Humidity	5% - 85%
Warranty	24months

Packing List

Barcode scanner×1pc, USB cable×1pc, Manul×1pc, Data base×1pc	
Inner box	1pc/box, 100 x 70 x 215mm, 0.3Kg
Out box	50pcs/ctn, 560 x 410 x 430mm, 16.8Kg