

# AW-8600 3inch Label Printer



## Specifications

Interfaces	USB / LAN / Bluetooth
Print Comand	CPCL / TSPL command (ESC/POS command)
Print Method	Direct Line Thermal
Print Speed	200mm/sec (MAX)
Resolution	203DPI (8dot/mm)
Inner Code	Supported 11 types font size
Print parameters	Support to download the Logo trademark
Media Sensor	Dual-media sensors: transmissive and reflective
Barcodes	1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D: QR Code, PDF417

## Paper

Thermal Paper Types	continuous paper, label paper, folded paper, tag paper
Effective Print Width	80mm (Max 576 points)
Available Max Paper Width	80±0.5mm
Paper Thickness	0.06-0.30 mm

## Package

Printer Dimension	160*110*93mm
Unit Weight	1.65kgs (with accessories)
Pieces Per CTN	12 Pieces
CTN Dimension	46.5 x 38x 47 cm
Gross Weight per CTN	21 kgs

## Environmental

Working Temperature	+0 °C ~ 50 °C (no condensation )
Working Humidity	20% ~ 85% RH (no condensation )
Storage Temperature	-20 °C ~ 60 °C (no condensation )
Storage Humidity	5% ~ 95% RH (no condensation )
Mechanical Noise	less than 60dB