

AW-8610 3 INCH BARCODE PRINTER



Specifications

Interfaces	USB / Bluetooth (optional)
Print Command	TSPL command (CPCL/ESC/POS command-optional)
Print Method	Direct Line Thermal
Print Speed	120mm/sec
TPH Life	50 KM
Resolution	203DPI (8dot/mm)
Inner Code	Supported 11 types font size
Print parameters	Support to download the Logo trademark
Media Sensor	Dual-media sensors: transmissive and reflective
Barcodes	1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D: QR Code, PDF417
Printer Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / WIN11 /MAC OS ; Support IOS / Android
Power Adapter	Input: AC 110V/220V, 50 ~ 60Hz ; Output: DC 24V/1.5A

Paper

Thermal Paper Types	continuous paper, label paper, folded paper, tag paper
Effective Print Width	20-80mm (Max 576 points)
Available Max Paper Width	76mm
Diameter of Paper Warehouse	100mm (MAX)
Paper Thickness	0.06-0.30 mm

Package

Printer Dimension	200*160*139.5mm
Unit Weight	1.40kgs (with accessories)
Pieces Per CTN	8 Pieces
Printer Color	Black / White
CTN Dimension	49 x 46 x 36 cm
Gross Weight	12 kgs

Environmental

Operating Temperature	+0 °C ~ 50 °C (no condensation allowed)
Working Humidity	20% ~ 85% RH (no condensation allowed)
Storage Temperature	-20 °C ~ 60 °C (no condensation allowed)
Storage Humidity	5% ~ 95% RH (no condensation allowed)
Mechanical Noise	less than 60dB (A weighted RMS)

Accessories

USB Cable	1 Piece
Power Adapter	1 Piece
Power Cable	1 Piece
Manual	1 Piece