

AW-9108RT

Wireless 1D Bar Code Scanner



Technology

Scan type	1D linear CCD
Interface	USB-HID USB-COM, RS232
Scan Mode	Manual/Auto scan/ Continue Scan
Scan Speed	300times/sec
Scanning angle	Skew $\pm 50^\circ$, Pitch $\pm 50^\circ$, Roll $\pm 30^\circ$
Minimum Resolution	4mil
Depth of Scan Field	10-600mm
Support Symbologies	UPC-A, UPC-E, EAN-8, EAN-13, ISSN, ISBN, Code 128, GS1-128, Code 39, Code 93, Code 11, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5, Industrial 2 of 5, Standard 2 of 5 (IATA), Codabar (NW-7), Plessey, MSI Plessey, RSS, etc.
Printing contrast	$\geq 25\%$
Wireless	2.4G, Bluetooth is optional, with charge base
Communicate distance	30-50m, with momery

Physical

Size	100mm x 72mm x 175mm (L xW xH)
Weight	205g
Material	ABS+PC
Cable Length	1.5m

Electronical

Voltage	5V
Working Current	220mA, Sleep current USB 30mA, RS232 2uA
Scanner Material	Eco-friendly, ABS+Rubber
Battery	1600mAh, after full charge continue use over 12hours

Environmental

Operation Temperature	-20 °C - 50°C
Storage Temperature	-40 °C - 70°C
Humidity	5% - 95%
Ambient lighting	0-100000LUX
Seismic resistance	3m
Warranty	24months

Packing List

Barcode scanner	×1pc, USB cable×1pc, USB receiver×1pc, Manul×1pc
Inner box	1pc/box, 100 x 80 x 240mm, 0.48Kg
Out box	50pcs/ctn, 560 x 410 x 430mm, 24Kg