

AW-9210 4inch Label Printer



Specifications

Interfaces	USB / LAN / Bluetooth / WIFI
Print Comand	TSPL command/CPCLcommand (ESC/POS command)
Print Method	Direct Line Thermal
Pirnt Speed	160mm/sec (MAX)
Resolution	203DPI (8dot/mm)
Inner Code	Supported 11 types font size
Print parameters	Support to download the Logo trademark
Media Sensor	Dual-media sensors: transmissive and reflective
One-dimensional code	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
Two-dimensional code	QR Code, PDF417
Printer Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / MACOS ; Support IOS / Android

Paper

Thermal Paper Types	continuous paper, label paper, folded paper, tag paper
Effective Print Width	100mm (Max 800 points)
Available Max Paper Width	110 ± 0.5mm
Paper Thickness	0.06-0.30 mm

Electrical

Charging Method	external charger DC 24V/2.5A
Print Head	Reliability
Print Reliability	10000000 pulse / dot or 50km

Physical

Printer Dimension	226*180*147mm
Unit Weight	1.9kgs (with accessories)
Pieces Per CTN	8 Pieces
Printer Color	White
CTN Dimension	60*39.6*35 cm
Gross Weight	15.5kgs

Environmental

Operating Temperature	+0 °C ~ 50 °C (no condensation allowed)
Working Humidity	20% ~ 85% RH (no condensation allowed)
Storage Temperature	-20 °C ~ 60 °C (no condensation allowed)
Storage Humidity	5% ~ 95% RH (no condensation allowed)
Mechanical Noise	less than 60dB (A weighted RMS)

Accessories

USB Cable	1 x 1M Cable
CD Driver	1 Piece
Power Adapter	1 Piece
Power Cable	1 Piece
Manual	1 Piece