

AW-9220 4inch Label Printer



Specifications

Print Method	Direct Line Thermal
Interfaces	USB / LAN / Bluetooth
Print Comand	TSPL(CPCL/ESC/POS compatible)
Pirnt Speed	Max to 160mm/s
Resolution	203DPI (8dot/mm)
Media Sensor	Transmissive and Reflective
Logo	support downloading and printing logo
Supported Font:	ASCII Font: 8*12, 9*17, 12*20, 12*24, 14*10, 14*25, 16*24, 21*27,24*32, 32*48 GB18030 font: 24*24 BIG5 Font: 24*24
Supported Code:	1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D: QR CODE,PDF417
Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / MACOS ; Support IOS / Android
Power	24V/2.5A DC charger
TPH Reliability	about 50km or 100millions pulses

Paper

Paper Types	continuous paper, label paper, folded paper, tag paper
Max paper roll	110*100mm (width*diameter)
Print Width	104mm (Max 800 points)
Paper Thickness	0.06-0.30 mm

Package

Printer Dimension	20*11.6*10.6cm
Printer N.W.	0.98KG
Package	1pc with accessories/box, 12boxes/ctn
Accessories	Manual, CD driver, USB Cable,Adapter, Power line
Box Dimension	21*18.5*12.6CM
Box G.W.	1.58Kgs
CTN Dimension	43.5*38.5*26.7 cm
CTN G.W.	20kgs

Environmental

Working Temperature	+0 °C ~ 50 °C (no condensation)
Working Humidity	20% ~ 85% RH (no condensation)
Storage Temperature	-20 °C ~ 60 °C (no condensation)
Storage Humidity	5% ~ 95% RH (no condensation)
Mechanical Noise	less than 60dB