

AW-Z230 80MM Thermal Bill Printer



Specifications:

Print Method	Direct Line Thermal
Interfaces	USB / LAN / Bluetooth (optional)
Print Comand	ESC / POS command
Print Speed	220mm/s
Resolution	203DPI (8dot/mm)
TPH Reliability	100km
Auto Cutter	Partial
Cutter Life	1.0 million cuts
Logo	support downloading and printing logo
Line Spacing	3.75mm (Adjustable by commands)
Extension Character Sheet	PC437 (Standard Europe) 、 Katakana、 PC850 (Multilingual) 、 PC860 (Portuguese) 、 PC863 (Canadian) 、 PC865 (Nordic) 、 West Europe、 Greek 、 Hebrew、 East Europe、 Iran、 WPC1252、 PC866 (Cyrillic#2) 、 PC852 (Latin2) 、 PC858、 IranII、 Latvian、 Arabic、 Thai、 PT151 (1251)
Character Size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, Traditional Chinese:3.0×3.0mm (24×24 dots)
Supported Code:	1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D: QR /PDF417
Input Buffer	96K bytes
NV Flash	256K bytes
Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / Linux ; Support IOS / Android
Power	Input: AC 110V/220V, 50 ~ 60Hz ; Output: DC 24V/1.5A

Paper

Paper Types	Thermal Roll Paper
Paper Width	79.5±0.5mm / φ 80 mm
Print Width	72mm
Paper Thickness	0.06-0.08 mm

Package

Printer Dimension	17.47*14.17*12.23cm
Printer N.W.	0.84 kg
Package	1pc with accessories/Box, 12 boxes/CTN
Accessories	Manual, USB Cable, Power Adapter, Paper Roll
Box Dimension	20.3*18.6*13.9 CM
Box G.W.	1.22 Kgs
CTN Dimension	61.4*38.8*29.8 CM
CTN G.W.	15Kgs

Environmental Requirements

Work Environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage Environment	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)
Mechanical Noise	less than 60dB